



Tumble Dryers

Tumble Dryers Economic Line

TUMBLE DRYER, SC-28 E ECONOMIC LINE

DIMENSIONS

		Article	Packed
Length	mm	985,00	1.090,00
Depth	mm	1.054,00	1.150,00
Height	mm	1.946,00	2.105,00
Weigth	Kg	350,00	390,00
Volumen	m3		3,10

ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		3x70+T - 180 A
400V - III+N		4x25+T - 125 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 66,00

TUMBLE DRYER, SC-28 E ECONOMIC LINE

Load Capacity : 31 kg. (load factor 1:18) or 25 kg (load factor 1:22).
 Production: + 55 kg/h.
 Galvanized steel body.
 Axial airflow.
 Time selector.
 Temperature selector.
 COOL DOWN at end of cycle.
 Lamp indicator ON and HEATING.
 Open door with safety device.
 EMERGENCY stop button.
 Frequency speed variator.
 Alarm noise indicator at end of cycle.
 Air extraction volume: 1500 m3/h.
 Drum in galvanized steel.
 IMPORTANT: Reversing drum.
 Drum volume: 550 litres.
 Diameter of door: 802 mm.
 Fluff filter in lower part .
 Transmission by means of pulleys.
 Main heating system: electric.
 Electrical connection : 400 V - III+N+ GROUND - 50/60 Hz.
 Heating power: 30 kW
 Total power: 31,15 kW.
 Dimensions: 985 x 1.054 x 1.946 mm

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	205	0	1.490		
EXHAUST	744	0	167	200 mm.	

