



Tumble Dryers

Tumble Dryers Green Evolution

STACK DRYER, SR-2-16 MP E

DIMENSIONS

		Article	Packed
Length	mm	785,00	880,00
Depth	mm	1.200,00	1.350,00
Height	mm	1.980,00	2.200,00
Weigth	Kg	190,00	225,00
Volumen	m3		1,98

ELECTRICITY

Electric power	KW	
230V -1+N		25,10
230V - III		NO
400V - III+N		3x10+T - 50 A
		4x6+T - 50 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 64,00

STACK DRYER, SR-2-16 MP E GREEN EVOLUTION

Total load capacity: 36 kg. (load factor 1:18) or 30 kg (load factor 1:22).

Production: + 66 kg/h.

External case made of skin plate, grey color, with stainless steel aesthetics.

Axial-radial airflow gives low energy consumption and a bigger drying efficiency.

Electronic microprocessor, with 10 preset programs and programmable by means of key.

LCD avec display of temperature and drying time.

Programmable time and temperature.

COOL DOWN at end of cycle.

Push -Pull button to START/STOP.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 870 m3/h.

IMPORTANT: Stainless steel drum.

IMPORTANT: Reversing drum .

Drum diameter: 750 mm

Depth of drum: 746 mm

Diameter of door: 574 mm.

reversible door hanging.

Microprocessor with diagnostic of mishaps, statistics of cycles...

Indicator of dirt in the filter.

Fluff filter in lower part .

Transmission by means of motoreducer .

Main heating system: electric.

Electrical connection : 400 V - III+N+ GROUND - 50/60 Hz.

Heating power: 2x18 kW

Total power: 37,10 kW.

Dimensions: 785 x 1.225 x 1.980 mm

OPTIONS:

- Humidity sensor with intelligent drying
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	528	0	821		0
EXHAUST	558	0	169	200 mm.	

