



Ironers & Flatwork Ironers

Flatwork ironers Ø 35

FLATWORK IRONER, PSE-35/200 MP

<u>DIMENSIONS</u>		Article	Packed
Length	mm	2.542,00	0,00
Depth	mm	660,00	0,00
Height	mm	1.112,00	0,00
Weigth	Kg	590,00	600,00
Volumen	m3	1,87	3,00

<u>ELECTRICITY</u>			
<u>Electric power</u>		KW	20,50
230V -1+N			NO
230V - III		OPT- 3x16+T - 63 A	
400V - III+N		4x6+T -32 A	

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

<u>LEVEL SOUND</u>	(dB)	63,00
--------------------	------	-------

FLAT WORK IRONER, PSE-35/200 MP
 Outer casing of white varnished steel.
 Return feed design requires minimum installation space.
 Steel roller.
 Strap feeding.
 NOMEX ironing straps.
 High throughput as linen is in contact with cylinder through a high proportion of the roller circumference.
 Safety protector for hands.
 Temperature control thermostat.
 Production: 30 / 35 kg/h.
 Roller length: 2.000 mm.
 Roller diameter: 325 mm.
 Ironing speed: 1 - 6,5 m/min.
 Ironing speed regulated by frequency variator.
 Temperature and speed MICROPROCESSOR CONTROL.
 Self auto diagnostic control.
 Automatic STOP by thermostat when roller is below 80 °C.
 HI -LIMIT safety thermostat.
 Exhaust sistem incorporated: 2 x 500 m3/h.
 Electric heating system.
 Heating power: 20 kW.
 Maximum power: 20,5 kW.
 Power intake: 400 V - III+N+T - 50 Hz.
 Dimensions: 2,542 x 660 x 1,112 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	2.472	0	130		0
EXHAUST	60	58	1.112	98	
EXHAUST	2.482	58	1.112	98	

