



## Ironers & Flatwork Ironers

Compact flatwork ironers, Phoenix series

### COMPACT FLATWORK IRONER, PSE-60/330/1-2 PL+AP

#### DIMENSIONS

		Article	Packed
Length	mm	4.300,00	4.400,00
Depth	mm	2.210,00	2.400,00
Height	mm	2.085,00	2.100,00
Weigth	Kg	3.300,00	3.350,00
Volumen	m3	19,81	22,18

#### ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		NO
400V - III+N	4x35+T - 125 A	

#### WATER

Not used

#### GAS

Not used

#### STEAM

Not used

#### AIR

Consumption	NI/min	21.000,00
Pressure	kg/cm2	7

#### LEVEL SOUND

(dB) 60,00

COMPACT FLATWORK IRONER, PHOENIX SERIES, PSE-60/330/1-2 PL+AP

Roller: Ø 600 mm - Length: 3.300 mm.

Production: 110 ÷ 140 kg/h.

Machine prepared to connect to a side stacker (not included).

High production machine, with a primary and cross folder.

You can work and fold in one or two different lanes, with a maximum width of 1.500 mm each one.

Maximum capacity for two primary and three cross folds.

Clothes outlet in the front part of the machine.

It is possible to choose the stacker's outlet side and direction.

Outer casing made of white-lacquered steel.

Control through a microprocessor (PLC) that allows folding automatically depending on the dimensions

of the clothes and creating up to 20 programs.

Optional vacuum table to improve and facilitate the incorporated feeding.

Optional partial by-pass.

Optional clothes rejection system through a push button.

Steel-coated roll. NOMEX - POLYESTER feeding straps.

Special NOMEX ironing straps.

Adjustable ironing speed between: 3 ÷ 18 m/min.

Safety protector for the hands.

Electronic thermostat and probe to adjust the temperature.

Incorporated extraction system: 2x1000 m3/h.

Necessary compressed air pressure: 7 bar.

Compressed air consumption: 21.000 NI/hour.

Electric heating system.

Heating power: 60 kW.

Maximum electrical power: 63,10 kW.

Dimensions: 4.300 x 2.210 x 2.085 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	245	0	210		
AIR	4.130	0	210	12 mm	
EXHAUST	1.260	560	1.900	120 mm	
EXHAUST	3.040	560	1.900	120 mm	

