



Ironers & Flatwork Ironers

Compact flatwork ironers, Poseidon series

COMPACT FLATWORK IRONER, PSE-60/330 PL

DIMENSIONS

		Article	Packed
Length	mm	4.390,00	4.500,00
Depth	mm	1.475,00	1.600,00
Height	mm	2.020,00	2.100,00
Weigth	Kg	2.850,00	2.900,00
Volumen	m3	13,08	15,12

ELECTRICITY

Electric power	KW	
230V - I+N		61,90
230V - III		NO
400V - III+N		NO
		4x35+T - 125 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Consumption	NI/min	9.000,00
Pressure	kg/cm2	7

LEVEL SOUND

(dB) 60,00

COMPACT FLATWORK IRONER, POSEIDON SERIES, PSE-60/330 PL

Roller: Ø 600 mm - Length: 3.300 mm.

Production: 110 ÷ 140 kg/h.

Poseidon series includes a lengthwise folder to make a maximum of two longitudinal pleats.

It works on 1 or 2 independent lanes.

Linen outlet in the front part of the machine, optional rear outlet.

Outer casing made of white-lacquered steel.

Control through a microprocessor (PLC).

Steel-coated roll.

NOMEX - POLYESTER feeding straps.

Special NOMEX ironing straps.

Adjustable ironing speed between: 3 ÷ 18 m/min.

Safety protector for the hands.

Electronic thermostat and probe to adjust the temperature.

Extraction system: 2 x 1000 m3/h.

Compressed air (necessary): 7 bar.

Compressed air consumption : 9.000 NI/h.

Electric heating system.

Heating power: 60 kW.

Maximum electrical power: 61,90 kW.

Dimensions: 4.390 x 1.475 x 2.020 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	380	0	170		
AIR	330	0	170	12 mm	
EXHAUST	290	165	1.800	120 mm	
EXHAUST	4.220	165	1.800	120 mm	

