



Tumble Dryers

Tumble Dryers Green Evolution

TUMBLE DRYER, SR-60 MP E

DIMENSIONS

		Article	Packed
Length	mm	1.270,00	1.340,00
Depth	mm	1.345,00	1.425,00
Height	mm	2.380,00	2.140,00
Weigth	Kg	550,00	575,00
Volumen	m3		4,08

ELECTRICITY

Electric power	KW	
230V -1+N		74,25
230V - III		NO
400V - III+N		3x120+T-300A
		4x50+T-160A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 66,00

TUMBLE DRYER, SR-60 MP E GREEN EVOLUTION

Load Capacity : 66.7 kg. (load factor 1:18) and 60.1 kg (load factor 1:20)
Production: + 120 kg/h.

External case made of skin plate, grey color, with stainless steel aesthetics.
Axial-radial airflow gives low energy consumption and a bigger drying efficiency.

Electronic microprocessor, with 10 preset programs and programmable by means of key.

LCD display of temperature and drying time.

Programmable time and temperature.

COOL DOWN at end of cycle.

Push -Pull button to START/STOP.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 3000 m3/h.

IMPORTANT: Stainless steel drum.

IMPORTANT: Reversing drum.

Drum diameter: 1225 mm.

Depth of drum: 1020 mm.

Diameter of door: 802 mm.

Microprocessor with diagnostic of mishaps, statistics of cycles...

Indicator of dirt in the filter.

Fluff filter in lower part.

Transmission by means of pulleys.

Main heating system: electric.

Electrical connection : 400 V - III+N+ GROUND - 50 Hz.

Heating power: 72 kW

Total power: 74,255 kW.

Dimensions: 1.270 x 1.345 x 2.380 mm

OPTIONS:

- Humidity sensor with intelligent drying
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel
- Marine version for ships (440 V III)

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	107	0	839		0
EXHAUST	1.008	0	230	300 mm.	

